

# CLS1410 Two Way Radios

## Activating Scan Setting

1. **Turn the radio off**
2. **Enter programming mode by doing the following**
  - a. Press and hold the PTT button and the MON button
  - b. Turn the radio on, keeping those buttons held down until you hear a chirp
  - c. If done successfully, you will see a PROG in the bottom left of the screen
3. **Adjust your settings**
  - a. Press the MENU button to cycle through your settings
    - i. 1<sup>st</sup> press will be to change the channel that you're adjusting settings for, to change press + or -
    - ii. 2<sup>nd</sup> press will be your frequency setting, to change press + or -
    - iii. 3<sup>rd</sup> press will be your code setting, to change press + or -
    - iv. 4<sup>th</sup> press will be your active channels, to change press + or -
    - v. 5<sup>th</sup> press will be your call tone, to change press + or -
    - vi. 6<sup>th</sup> press will be your mic gain, to change press + or -
    - vii. **7<sup>th</sup> press will be your scan settings** (you will see a z shape on the bottom of the screen), to change please follow these steps:
      1. Press + or - to change the channel number that you need to enable/disable the scan feature
      2. To enable/disable a specific channel, press the **MON** button to select Y (yes) or N (no) for that channel
      3. Cycle through all 4 channels and enable/disable the specific channels desired
4. **Save your settings**
  - a. To save your settings, press and hold the PTT button until you hear a low pitch beep. The PROG on the screen will go away.
5. **Activating after programming**
  - a. Turn radio ON
  - b. With radio on, switch to your designated channel that you usually stay on
  - c. Short press the MON button to enable/disable the scan feature. You can press the PTT to transmit while scan mode is activated and your radio will transmit on your designated channel (see b above)



PTT

MON

MENU

+ OR -